



skf P 35 RM Ball bearing plummer block units

Bearing No. P 35 RM

Bore Diameter	35 mm
d	35 mm
s1	23,3 mm
A	41 mm
A1	27 mm
B	33 mm
H	78 mm
H1	39,2 mm
H2	5 mm
J	106 mm
L	130 mm
N	11,2 mm
Thread (G)	10
Weight	0,57 Kg
Basic dynamic load rating (C)	25,5 kN
Basic static load rating (C0)	15,3 kN
Housing material	Pressed steel
A ₁	27 mm
B ₄	6 mm
H ₁	39.3 mm
H ₂	5 mm
s ₁	23.3 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C ₀	15.3 kN
Fatigue load limit P _u	0.655 kN
Permissible radial housing	3.3 kN

P 35 RM Bearing 2D drawings and 3D CAD models



NTN BEARING MANUFACTURING DE MEXICO,S...

load max.	
Limiting speed	5300 r/min
Mass bearing unit	0.58 kg
Thread grub screw G ₂	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in