



skf SY 55 TF Ball bearing plummer block units

Bearing No. SY 55 TF

SY 55 TF Bearing 2D drawings and 3D CAD models

Bore Diameter	55 mm
d	55 mm
s1	33,4 mm
A	60 mm
A1	40 mm
B	55,6 mm
G	16 mm
H	126 mm
H1	63,5 mm
H2	24 mm
J	171,5 mm
L	219 mm
N	27,5 mm
N1	18 mm
Weight	3,6 Kg
Basic dynamic load rating (C)	43,6 kN
Basic static load rating (C0)	29 kN
Fatigue load limit (Pu)	1,25
Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.61
EAN	7316577030856
Product Group	M06110
Number of Mounting Holes	2



NTN BEARING MANUFACTURING DE MEXICO,S...

Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 211-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Standard Duty Wide Inner Race Y Bearing Has Flinger
Long Description	2 Bolt Pillow Block; 55MM Bore; 63.5MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubricatable; Cast Iron; M Seal; Non-expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SY 55 TF
Weight / LBS	7.94
Actual Bolt Center to Center	6.8 Inch 171.5Millimeter
Base to Center Height	2.5 Inch 63.5 Millimeter
Length Thru Bore	2.189 Inch 55.6 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Bore	2.165 Inch 55 Millimeter



NTN BEARING MANUFACTURING DE MEXICO,S...

Nominal Bolt Center to Center	6.8 Inch 171.5 Millimeter
Bolt Spacing Minimum	0 Inch 0 Millimeter
mounting:	Two-Bolt Base
overall width:	40 mm
bore diameter:	55 mm
radial dynamic load capacity:	43.6 kN
bore type:	Round
radial static load capacity:	29 kN
base to bore centerline:	2.5000 in
base width:	60 mm
housing material:	Cast Iron
bolt center-to-center length:	171.5 mm
locking device:	Set Screw
maximum rpm:	3600 RPM
expansion type:	Non-Expansion Bearing (Fixed)
lubrication type:	Lubrication Fitting
overall length:	219 mm
series:	SY
overall height:	126 mm
replacement bearing:	YAR 211-2F
finish/coating:	Uncoated
standards met:	ISO
Housing material	Cast iron
A ₁	40 mm
A ₅	34 mm
B ₄	9 mm
H ₁	63.5 mm
H ₂	24 mm
J max.	181 mm
J min.	162 mm



NTN BEARING MANUFACTURING DE MEXICO,S...

N_1	18 mm
s_1	33.4 mm
R_G	1/4-28 UNF
R_1	4.5 mm
R	45 °
D_N	6.5 mm
SW_N	7 mm
G_N	1/4-28 SAE-LT
J_6	201 mm
J_7	21 mm
N_4	4 mm
Basic dynamic load rating C	43.6 kN
Basic static load rating C_0	29 kN
Fatigue load limit P_u	1.25 kN
Limiting speed	3600 r/min
Mass bearing unit	3.3 kg
Thread grub screw G_2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N · m
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in